## **Mini Compact Stand (Black Aluminum)** MU010AB0000



## **Description**

Our Mini Compact Stand is one of the most reliable compact stands for location and professional studio services, thanks to the wide support base of the three .8" (20 mm) diameter legs. The wide support makes it suitable for supporting diffuser umbrellas and backlights, LED luminaires for shooting video, flash photography, microphones, surveillance cameras, and LED levels.

The Mini Compact Stand is the ideal article for video kits. The lightweight and overall dimensions of this stand, made of electro-welded aluminum tube in the MU010AB and MU010A versions, guarantee its handling and transportability for on-site services as well as stability and safety.

There is a steel version, MU010SB, which ensures a higher payload (up to 15.4lbs or 7 kg) than the aluminum model, and is an excellent response to the needs of video shooting in the studio or on location, with the weight and overall dimensions of a lightweight compact stand.

Mini compact stand sleeves and crossbars are made of die-cast aluminum. None of the elements are made of thermoplastic material, except for the knobs.

The clamping joints are equipped with a device that guarantees the locking of the tube with minimum rotation of the knob.

It is possible to install wheels for handling and pneumatic system (air cushion) to control the descent of the rods under load.





## **Features**

CLOSED LENGTH  MINIMUM HEIGHT  MAX HEIGHT  P1 in (230 cm)  LOAD AT MAXIMUM EXTENSION  8 lb 13 oz (4 kg)  WEIGHT  2 lb 7 oz (1.1 kg)  MATERIAL  Aluminum  COLOR FINISH  Black  SECTIONS  4  RISE NUMBER  3  SECTION DIAMETER  1/.866/.709/.591 in (25,4/22/18/15 mm)  LEG SHAPE  MAXIMUM OPENING  179 in (20 mm) diameter  MAXIMUM OPENING  SPIGOT TYPE  Type 2  WHEELS  Available  AIR CUSHIONED	reatures	
MAX HEIGHT 91 in (230 cm)  LOAD AT MAXIMUM EXTENSION 8 lb 13 oz (4 kg)  WEIGHT 2 lb 7 oz (1.1 kg)  MATERIAL Aluminum  COLOR FINISH Black  SECTIONS 4  RISE NUMBER 3  SECTION DIAMETER 1/.866/.709/.591 in (25,4/22/18/15 mm)  LEG SHAPE .79 in (20 mm) diameter  MAXIMUM OPENING 37.4 in (95 cm)  LEVELING LEG No  SPIGOT TYPE Type 2  WHEELS Available	CLOSED LENGTH	28 in (70 cm)
LOAD AT MAXIMUM EXTENSION  8 lb 13 oz (4 kg)  WEIGHT  2 lb 7 oz (1.1 kg)  MATERIAL  Aluminum  COLOR FINISH  Black  SECTIONS  4  RISE NUMBER  3  SECTION DIAMETER  1/.866/.709/.591 in (25,4/22/18/15 mm)  LEG SHAPE  MAXIMUM OPENING  179 in (20 mm) diameter  MAXIMUM OPENING  37.4 in (95 cm)  LEVELING LEG  NO  SPIGOT TYPE  Type 2  WHEELS  Available	MINIMUM HEIGHT	31 in (80 cm)
WEIGHT 2 lb 7 oz (1.1 kg)  MATERIAL Aluminum  COLOR FINISH Black  SECTIONS 4  RISE NUMBER 3  SECTION DIAMETER 1/.866/.709/.591 in (25,4/22/18/15 mm)  LEG SHAPE .79 in (20 mm) diameter  MAXIMUM OPENING 37.4 in (95 cm)  LEVELING LEG No  SPIGOT TYPE Type 2  WHEELS Available	MAX HEIGHT	91 in (230 cm)
MATERIAL Aluminum  COLOR FINISH Black  SECTIONS 4  RISE NUMBER 3  SECTION DIAMETER 1/.866/.709/.591 in (25,4/22/18/15 mm)  LEG SHAPE .79 in (20 mm) diameter  MAXIMUM OPENING 37.4 in (95 cm)  LEVELING LEG No  SPIGOT TYPE Type 2  WHEELS Available	LOAD AT MAXIMUM EXTENSION	8 lb 13 oz (4 kg)
COLOR FINISH  SECTIONS  4  RISE NUMBER  3  SECTION DIAMETER  1/.866/.709/.591 in (25,4/22/18/15 mm)  LEG SHAPE  MAXIMUM OPENING  179 in (20 mm) diameter  MAXIMUM OPENING  179 in (95 cm)  LEVELING LEG  NO  SPIGOT TYPE  Type 2  WHEELS  Available	WEIGHT	2 lb 7 oz (1.1 kg)
SECTIONS  RISE NUMBER  3  SECTION DIAMETER  1/.866/.709/.591 in (25,4/22/18/15 mm)  LEG SHAPE  MAXIMUM OPENING  179 in (20 mm) diameter  MAXIMUM OPENING  37.4 in (95 cm)  LEVELING LEG  NO  SPIGOT TYPE  Type 2  WHEELS  Available	MATERIAL	Aluminum
RISE NUMBER  SECTION DIAMETER  1/.866/.709/.591 in (25,4/22/18/15 mm)  LEG SHAPE  .79 in (20 mm) diameter  MAXIMUM OPENING  37.4 in (95 cm)  LEVELING LEG  NO  SPIGOT TYPE  Type 2  WHEELS  Available	COLOR FINISH	Black
SECTION DIAMETER  1/.866/.709/.591 in (25,4/22/18/15 mm)  LEG SHAPE  .79 in (20 mm) diameter  MAXIMUM OPENING  37.4 in (95 cm)  LEVELING LEG  No  SPIGOT TYPE  Type 2  WHEELS  Available	SECTIONS	4
LEG SHAPE  .79 in (20 mm) diameter  MAXIMUM OPENING  37.4 in (95 cm)  LEVELING LEG  No  SPIGOT TYPE  Type 2  WHEELS  Available	RISE NUMBER	3
MAXIMUM OPENING 37.4 in (95 cm)  LEVELING LEG No  SPIGOT TYPE Type 2  WHEELS Available	SECTION DIAMETER	1/.866/.709/.591 in (25,4/22/18/15 mm)
LEVELING LEG No SPIGOT TYPE Type 2 WHEELS Available	LEG SHAPE	.79 in (20 mm) diameter
SPIGOT TYPE Type 2 WHEELS Available	MAXIMUM OPENING	37.4 in (95 cm)
WHEELS Available	LEVELING LEG	No
	SPIGOT TYPE	Type 2
AIR CUSHIONED Available	WHEELS	Available
	AIR CUSHIONED	Available