

RETRO-Passive® 700

700W Incandescent Replacement LED Engine
120V • 277V • 240VAC • CSA

CANTOUSA
INNOVATIVE LIGHTING PRODUCTS

Energy efficient LED Light Engine

Designed to retrofit directly into existing fixtures.

The RETRO-Passive is a CSA listed, Energy Star 2.0 retrofit kit that rapidly transforms existing inefficient incandescent fixtures into energy efficient LED fixtures. Our patented technology allows the fixture to smoothly dim from 0-100% utilizing existing dimming technology. Retrofit kits are available with a variety of options for both recessed and pendant style fixtures. Installation is as easy as changing a light bulb. Our LED technology creates even fields and delivers consistent color. The RETRO-Passive 700 delivers more light than most 700 watt incandescent bulbs it replaces with only a 72 watt load.

**10 Year
LED Array
Warranty**



What the RETRO IS

- More cost effective than fixture replacement
- Large lumen output for this section of the market
- Listed for screw in replacement
- Energy Star certified 2.0
- Dims on existing dimming systems with no additional installation of control system
- 0-100% dimming without flicker, pulse, or stepping
- 80+ High CRI

Electrical Data

- 72 Watts (72.3)
- Power Factor (PF) .9955
- Lumens: 8107 @ 2700K
- Lumens per watt: 112.3
- LM 70: >50,000 Hours
- CRI@2700K: 81.11, R9+1.8
- 5 lbs 6.4 oz w/Reflector

Applications

- 10 feet to 60 feet high ceilings
- Where dimming is a key concern
- Where there is no desire or budget to replace existing fixtures
- Where access is limited
- Where Energy Star is required
- Where a custom solution is required
- Where the ceiling cannot be disturbed

Typical Installations

- Auditoriums
- Houses of worship
- Arenas
- Lobbies
- Museums
- Educational facilities
- Convention centers
- Concert halls

Base Types

E26- Edison
Par Ring/Bare Wire
Bi Pin
Custom Options

CCT Lumen Output

2700K: 8107 Lumens
3000K: 8489 Lumens
3500K: 8669 Lumens
4000K: 8769 Lumens
5000K: 8902 Lumens

Fixture Lenses

Tall 15 Degrees
Tall 23 Degrees
Tall 46 Degrees
Short 26 Degree
Short 40 Degree
Short 59 Degrees
Short 70 Degrees
None 120 Degrees

Color Temp

2700K -
3000K - Standard
3500K -
4000K -
5000K -

Order Guide

	-		-		-		-		-		-		-		-	
--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--

Fixture Type	Base Type	Color Temp	CRI*	Optics	Accessories	Housings	Warranty
R700 - P	E11 1 3/4" 2 3/4" 4"	2700K 3000K 3500K 4000K 5000K	80, 90, 97 80, 90, 97 80, 90 80, 90, 97 80, 90	Tall 15 Tall 23 Tall 46 Short 26 Short 40 Short 59 Short 70 NONE- 120 Degrees	Diffuser E26 Extender 1" E26 Extender 2" Lift Plate (1/2") PAR Ring (56) Custom Plate	Pendant Large Pendant Small Recessed Can PAR56 PAR Can Black or Silver PAR64 PAR Can Black or Silver	10 Year LED Array 3 Year Standard +1 +2 +3 +4 +5 +6 +7
	E26 1" 1 1/2" 2 1/2"						
	E39 - Mogul *						
	BD15A *						
	Specific Height						
	BW - Bare Wire						
	PP - PAR Plug						
	JBox**						

*E39 and BD15A require an E26 base with adaptors used to make this unit compatible with these base types. **JBox includes Bare Wire.

* Chips with a CRI greater than 80 are an additional 6 weeks beyond standard delivery




RETRO-Passive® 700

700W Incandescent Replacement LED Engine
120V • 277V • 240VAC • CSA

CANTOUSA
INNOVATIVE LIGHTING PRODUCTS

Fixture Drawing



Photometrics (R700) 3,000K

Multiplication Factor for Color Temperature

- to convert to 2,700 Kelvin - fc X .9488
- to convert to 3,500 Kelvin - fc X 1.0196
- to convert to 4,000 Kelvin - fc X 1.0439
- to convert to 5,000 Kelvin - fc X 1.0617

To Solve Footcandles
Over A Distance

To Solve Area Over A
Distance

Peak Output
(Distance X Distance)

Distance X Mult.Factor

Mult. Factor 0.4617 Distance	26° Diameter	Peak Output 20,738fc Foot Candles	Mult. Factor 0.7279 Distance	40° Diameter	Peak Output 12,936fc Foot Candles	Mult. Factor 1.1315 Distance	59° Diameter	Peak Output 8,341c Foot Candles	Mult. Factor 1.4004 Distance	70° Diameter	Peak Output 4,489c Foot Candles
8'	4'	331	8'	6'	204	8'	9'	130	8'	11'	73
10'	5'	216	10'	7'	134	10'	11'	85	10'	14'	48
20'	9'	51	20'	15'	32	20'	23'	21	20'	28'	11
30'	14'	22	30'	22'	14	30'	34'	9	30'	42'	5
40'	18'	12	40'	29'	7	40'	45'	5	40'	56'	2
Mult. Factor 0.2633 Distance	15° Diameter	Peak Output 37,197fc Foot Candles	Mult. Factor 0.4069 Distance	23° Diameter	Peak Output 24,838fc Foot Candles	Mult. Factor .8489 Distance	46° Diameter	Peak Output 8,872fc Foot Candles	Mult. Factor 3.4641 Distance	120° Diameter	Peak Output 2,962fc Foot Candles
8'	2'	600	8'	3'	400	8'	7'	142	8'	28'	46
10'	3'	310	10'	4'	262	10'	8'	100	9'	31'	38
20'	5'	90	20'	8'	61	20'	17'	21	10'	35'	30
30'	8'	39	30'	12'	26	30'	25'	10	12'	42'	21
40'	11'	22	40'	16'	14	40'	34'	5	15'	52'	13
									20'	69'	7

Contact your local representative or dealer for IES files.



1092 West Atlanta Street, SE • Suite 600 • Marietta, GA 30060 • 888-252-5912 • info@cantousa.com • cantousa.com

V 1.6 12/07/20